

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) A laser irradiation apparatus comprising:
 - a first laser oscillator;
 - a second laser oscillator;
 - a slit for blocking an end portion of a first laser beam emitted from the first laser oscillator;
 - a condensing lens;
 - means for delivering a second laser beam emitted from the second laser oscillator so as to cover a range irradiated with the first laser beam on an irradiation surface;
 - means for moving the irradiation surface in a first direction relative to the first laser beam and the second laser beam; and
 - means for moving the irradiation surface in a second direction relative to the first laser beam and the second laser beam,
 - wherein the first laser oscillator and the second laser oscillator are pulsed lasers having a repetition rate of 10 MHz or more,
 - wherein the first laser beam is a harmonic and the second laser beam is a fundamental wave, and
 - wherein a laser spot of the second laser beam covers the whole beam spot of the first laser beam on the irradiation surface.

2. (Previously Presented) A laser irradiation apparatus comprising:
 - a first laser oscillator;
 - a second laser oscillator;

a diffractive optical element;

a slit for blocking an end portion of a first laser beam emitted from the first laser oscillator;

a condensing lens;

means for delivering a second laser beam emitted from the second laser oscillator so as to cover a range irradiated with the first laser beam on an irradiation surface after passing through the diffractive optical element;

means for moving the irradiation surface in a first direction relative to the first laser beam and the second laser beam; and

means for moving the irradiation surface in a second direction relative to the first laser beam and the second laser beam,

wherein the first laser oscillator and the second laser oscillator are pulsed lasers having a repetition rate of 10 MHz or more,

wherein the first laser beam is a harmonic and the second laser beam is a fundamental wave, and

wherein a laser spot of the second laser beam covers the whole beam spot of the first laser beam on the irradiation surface.

3. (Previously Presented) The laser irradiation apparatus according to Claim 1 or 2, wherein the harmonic is obtained by converting the first laser beam by a non-linear optical element.

4. (Canceled)

5. (Previously Presented) The laser irradiation apparatus according to Claim 1 or 2,

wherein the first laser oscillator and the second laser oscillator are pulsed lasers having a medium of a single-crystal YAG, YVO₄, YLF, YAlO₃, or GdVO₄, or a poly-

crystal YAG, Y_2O_3 , YVO_4 , $YAlO_3$, or $GdVO_4$, each of which is added with one or plural elements selected from the group consisting of Nd, Yb, Cr, Ti, Ho, Er, Tm, and Ta as dopant.

6. (Previously Presented) The laser irradiation apparatus according to Claim 1 or 2, wherein the condensing lens is a cylindrical lens or a spherical lens.

7. (Previously Presented) The laser irradiation apparatus according to Claim 1 or 2, wherein the first direction and the second direction intersect with each other.

8. (Currently Amended) A laser irradiation method comprising:
emitting a first laser beam from a first laser oscillator;
passing the first laser beam through a slit to form a second laser beam;
condensing the second laser beam by a condensing lens to form a third laser beam;
delivering the third laser beam to an irradiation surface;
delivering a fourth laser beam emitted from a second laser oscillator so as to cover the third laser beam on the irradiation surface; and
scanning the third laser beam and the fourth laser beam relative to the irradiation surface,
wherein the first laser oscillator and the second laser oscillator are pulsed lasers having a repetition rate of 10 MHz or more,
wherein the first laser beam is a harmonic and the second laser beam is a fundamental wave, and
wherein a laser spot of the ~~second~~ third laser beam covers the whole beam spot of the ~~first~~ fourth laser beam on the irradiation surface.

9. (Currently Amended) A laser irradiation method comprising:

emitting a first laser beam from a first laser oscillator;
passing the first laser beam through a diffractive optical element to form a second laser beam;
passing the second laser beam through a slit to form a third laser beam;
condensing the third laser beam by a condensing lens to form a fourth laser beam;
delivering the fourth laser beam to an irradiation surface;
delivering a fifth laser beam emitted from a second laser oscillator so as to cover the fourth laser beam on the irradiation surface; and
scanning the fourth laser beam and the fifth laser beam relative to the irradiation surface,
wherein the first laser oscillator and the second laser oscillator are pulsed lasers having a repetition rate of 10 MHz or more,
wherein the first laser beam is a harmonic and the second laser beam is a fundamental wave, and
wherein a laser spot of the ~~second~~ fifth laser beam covers the whole beam spot of the ~~first~~ fourth laser beam on the irradiation surface.

10. (Previously Presented) The laser irradiation method according to Claim 8 or 9, wherein the harmonic is obtained by converting the first laser beam by a non-linear optical element.

11. (Canceled)

12. (Previously Presented) The laser irradiation method according to Claim 8 or 9,

wherein the first laser oscillator and the second laser oscillator are pulsed lasers having a medium of a single-crystal YAG, YVO₄, YLF, YAlO₃, or GdVO₄, or a polycrystal YAG, Y₂O₃, YVO₄, YAlO₃, or GdVO₄, each of which is added with one or plural

elements selected from the group consisting of Nd, Yb, Cr, Ti, Ho, Er, Tm, and Ta as dopant.

13. (Previously Presented) The laser irradiation method according to Claim 8 or 9, wherein the condensing lens is a cylindrical lens or a spherical lens.

14. (Canceled)

15. (Previously Presented) A laser irradiation apparatus comprising:

a first laser oscillator;

a second laser oscillator;

a slit for blocking end portions of a first laser beam emitted from the first laser oscillator;

an optical fiber for delivering a second laser beam emitted from the second laser oscillator so as to cover a range irradiated with the first laser beam on an irradiation surface,

wherein the first laser oscillator and the second laser oscillator are pulsed lasers having a repetition rate of 10 MHz or more,

wherein the first laser beam is a harmonic and the second laser beam is a fundamental wave, and

wherein a laser spot of the second laser beam covers the whole beam spot of the first laser beam on the irradiation surface.